AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (original) A method for manufacturing electron emitters by providing pairs of element electrodes, and conductive layers connecting the element electrodes to each other on a substrate, the method comprising:

a step of forming banks surrounding electrode-forming regions for forming the element electrodes and conductive layer-forming regions for forming the conductive layers;

a step of discharging first droplets toward the electrode-forming regions; and a step of discharging second droplets toward the conductive layer-forming regions.

- 2. (original) The method for manufacturing electron emitters according to Claim 1, further comprising a step of lyophobing the banks.
- 3. (original) The method for manufacturing electron emitters according to Claim 1, wherein the banks are formed using a lyophobic material.
- 4. (original) The method for manufacturing electron emitters according to Claim 1, further comprising a step of lyophilizing at least one of the electrode-forming region and the conductive layer-forming region.

- 5. (original) An electron emitter manufactured by the method according to Claim 1.
 - 6. (original) An electron emitter comprising:
 - a substrate;
 - a pair of element electrodes;
 - a conductive layer connecting the element electrodes to each other; and
 - a bank surrounding the element electrodes and the conductive layer,

wherein the element electrodes, the conductive layer, and the bank are disposed on the substrate.

- 7. (original) An electro-optical device comprising the electron emitter according to Claim 6.
- 8. (original) An electronic apparatus comprising the electro-optical device according to Claim 7.
- [[8.]] 9. (currently amended) A method for manufacturing an electron emitter comprising:

defining a pair of spaced apart electrode-forming regions on a substrate;

defining a conductive layer-forming region on the substrate, the conductive layerforming region interconnecting the electrode-forming regions;

forming a bank encircling the electrode-forming regions and the conductive layerforming region;

discharging first droplets toward the electrode-forming regions to form a pair of element electrodes; and

discharging second droplets toward the conductive layer-forming regions to form a conductive layer connecting the element electrodes to each other.

[[9.]] 10. (currently amended) The method of claim [[8]] 9 further comprising treating a portion of the conductive layer to form an electron-emitting section.

[[10.]] 11. (currently amended) The method of claim [[8]] 9 further comprising removing the bank after the conductive layer and element electrodes are formed.

[[11.]] <u>12</u>. (currently amended) The method of claim [[8]] <u>9</u> further comprising rendering the bank lyophobic.

[[12.]] 13. (currently amended) The method of claim [[8]] 9 further comprising rendering at least one of:

the electrode-forming regions; and

the conductive layer-forming region;

lyophilic.

REMARKS

Minor amendments have been made to the claims to simply correct the misnumbering of claim 8 in the original application. If the Examiner believes that personal communication will expedite prosecution of this application, the Examiner is invited to telephone the undersigned at (248) 641-1600.

Ву:

Respectfully submitted,

Dated: August 9, 2004

HARNESS, DICKEY & PIERCE, P.L.C. P.O. Box 828 Bloomfield Hills, Michigan 48303 (248) 641-1600

GGS/jb

Serial No. 10/809,203